

Product	Axle Model	Ratings		Ratios	Axle Shaft			Nominal Ring Gear Diameter in. [mm]	Axle Housing			Wheel-end Series	Options			
		Max. GAW lbs. [kg]	Max. GCW** Turnpike lbs. [kg]		Body Diameter in. [mm]	Number of Splines	Spline Diameter in. [mm]		Box Section Width in. [mm]	Box Section Height in. [mm]	Wall Thickness at Spring Seat in. [mm]		Thickwall Housing in. [mm]	Differential Lock	SelectTrac	Pump
EconoTrek 6x2	S21-172 and S20-045B	40,000 [18,144]	100,000 [45,359]	3.07, 3.21, 3.42, 3.58, 3.73, 3.91, 4.10, 4.30, 4.56, 4.78, 5.25, 5.38, 5.57, 6.14	2.06 [52]	46	2.35 [60]	17.3 [440]	4.61 [117]	5.24 [134]	0.43 [11] and 0.37 [9.5]	R	0.50 [12.5]			
	S21-175 and S20-045B		115,000 [52,163]	1.95, 2.05, 2.16, 2.31, 2.47, 2.64, 2.85, 3.07, 3.42				17.9 [455]					0.50 [12.5]		Requires 0.5 [12.5] and 0.43 [11] wall thickness	

Rating is subject to Dana engineering application approval. \*\* For 3% max. grade.



January 2021