

Axle Model	Ratings		Ratios	Axle Shaft			Nominal Ring Gear Diameter in. [mm]	Axle Housing			Spindle Type	Options				
	Max. GAW lbs. [kg]	Max. GCW HWY lbs. [kg]		Body Diameter in. [mm]	Number of Splines	Spline Diameter in. [mm]		Box Section Width in. [mm]	Box Section Height in. [mm]	Wall Thickness at Spring Seat in. [mm]		SelectTrac™	Differential Lock	Electromagnetic Retarder	No Spin Differential	
S21-190	21,000 [9,525]	125,000 [56,699]	3.58, 3.73, 3.91, 4.10, 4.30, 4.56, 4.78, 5.25, 5.38, 5.57, 6.14, 6.83, 7.17, 7.83	2.06 [52]	46	2.35 [60]	18.5 [470]	4.61 [117]	5.24 [134]	0.43 [11]	R					
S23-190	23,000 [10,433]			0.50 [12.5]												
S26-190	26,000 [11,793]		3.42, 3.58, 3.73, 3.91, 4.10, 4.30, 4.56, 4.78, 5.25, 5.38, 5.57, 6.14, 6.83, 7.17, 7.83	2.25 [57]				5.31 [135]	5.91 [150]	0.63 [16]		W				
S30-190	30,000 [13,608]															

Rating is subject to Dana engineering application approval

